

LT-24-24-RGB+W-2400



Product Specifications:

| | |
|--------------------|--|
| Product Range | Standard Linear |
| LED Strip Type | RGB+W |
| LED Pitch | 10.4 mm |
| LED's per metre | 192 |
| LED Cut Point | 62.5 mm |
| Dimensions | 12 mm x 2 mm x 30 m <i>(Reel length)</i> |
| Colour Temperature | RGB+W (2400K) |
| Lifetime | Up to 26300 hours |
| Mounting Method | 3M™ VHB Tape |

Product Performance: *(Based on 1000mm)*

| | | | | |
|------------------------|---|--------|-------|-------------|
| Voltage | 24 V | | | |
| Power Consumption | 24 W | | | |
| Power Split | Red | Green | Blue | White 2400K |
| | 4.8 W | 4.8 W | 4.8 W | 9.6 W |
| Lumen Output | 1500 lumens | | | |
| Lumen Split | Red | Green | Blue | White 2400K |
| | 130 lm | 302 lm | 68 lm | 912 lm |
| Lumen Efficiency | 62.5 lumens / W | | | |
| Maximum Continuous Run | 3 metres <i>(Powered from one end)</i> | | | |
| IP Rating | IP 20 <i>(Other IP ratings available)</i> | | | |
| CRI | 90+ Ra <i>(95+ Ra available)</i> | | | |
| Colour Binning Step | 3 SCDM <i>(2 SCDM available)</i> | | | |
| LED Beam Angle | 120 ° | | | |
| Operating Temperature | -20°C ~ +50°C | | | |

Product Dimensions: *(Units in mm)*

