# LT-24-24-RGB+W-4000

CE   RoHS   cULus LISTED   LM-80 Tested

## Product Specifications:

| | |
|---|---|
| Product Range | Standard Linear |
| LED Strip Type | RGB+W |
| LED Pitch | 10.4 mm |
| LED's per metre | 192 |
| LED Cut Point | 62.5 mm |
| Dimensions | 12 mm x 2 mm x 30 m *(Reel length)* |
| Colour Temperature | RGB+W (4000K) |
| Lifetime | Up to 26300 hours |
| Mounting Method | 3M™ VHB Tape |

## Product Performance: *(Based on 1000mm)*

| | | | | |
|---|---|---|---|---|
| Voltage | 24 V | | | |
| Power Consumption | 24 W | | | |
| Power Split | Red | Green | Blue | White 4000K |
| | 4.8 W | 4.8 W | 4.8 W | 9.6 W |
| Lumen Output | 1500 lumens | | | |
| Lumen Split | Red | Green | Blue | White 4000K |
| | 130 lm | 302 lm | 68 lm | 1018 lm |
| Lumen Efficiency | 62.5 lumens / W | | | |
| Maximum Continuous Run | 3 metres *(Powered from one end)* | | | |
| IP Rating | IP 20 *(Other IP ratings available)* | | | |
| CRI | 90+ Ra *(95+ Ra available)* | | | |
| Colour Binning Step | 3 SCDM *(2 SCDM available)* | | | |
| LED Beam Angle | 120 ° | | | |
| Operating Temperature | -20°C ~ +50°C | | | |

## Product Dimensions: *(Units in mm)*



62.5   10.4   12   2