LT-48-8-56-RGBW-4500



Product Specifications:

| Product Range | 48 V Linear |
|--------------------|-----------------------------------|
| LED Strip Type | RGBW |
| LED Pitch | 17.9 mm |
| LED's per metre | 56 |
| LED Cut Point | 250 mm |
| Dimensions | 16 mm x 2 mm x 30 m (Reel length) |
| Colour Temperature | RGBW (4500K) |
| Lifetime | Up to 43800 hours |
| Mounting Method | 3M™ VHB Tape |

Product Performance: (Based on 1000mm)

| Voltage | 24 V | | | |
|------------------------|------------------------------------|--------|--------|-------------|
| Power Consumption | 7.68 W | | | |
| Danier Culit | Red | Green | Blue | White 4500K |
| Power Split | 1.56 W | 1.56 W | 1.56 W | 3 W |
| Lumen Output | 541 lumens | | | |
| Lumen Split | Red | Green | Blue | White 4500K |
| | 70 lm | 219 lm | 40 lm | 218 lm |
| Lumen Efficiency | 70.4 lumens / W | | | |
| Maximum Continuous Run | 5 metres (Powered from one end) | | | |
| IP Rating | IP 20 (Other IP ratings available) | | | |
| CRI | 90+ Ra (95+ Ra available) | | | |
| Colour Binning Step | 3 SCDM (2 SCDM available) | | | |
| LED Beam Angle | 120° | | | |
| Operating Temperature | -20°C ~ +50°C | | | |

Product Dimensions: (Units in mm)

